



## SAFETY DATA SHEET

### Section 1. Identification of the material and the supplier

Product: **Holts Tyreweld**

Product Code: HT5SFKY6,

Product Use: Emergency Puncture Repair

Restriction of Use: Refer to Section 15

New Zealand Supplier:

**Filpro Automotive NZ Ltd**

Address:

40 Firth St Drury  
Auckland

Telephone:

+64 9 2946752

Fax Number:

+64 9 2946751

**Emergency Telephone:**

**0800 764 766 (National Poison Centre)**

Manufacturer:

Holt Lloyd International

Address:

Barton Dock Road  
Manchester M32 0YQ England

Inquires

+44 161 866 4800

Date of SDS Preparation:

04 March 2021

### Section 2. Hazards Identification

**This substance is hazardous according to the *HSNO (Minimum Degrees of Hazard) Regulations 2001***

**EPA Approval No: Aerosols (Flammable) – HSR002515**

#### Pictograms



Flammable



Irritant

Signal Word: DANGER

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
2.1.2A	H222	Extremely flammable aerosol.	Category 1
6.1D (inhalation)	H332	Harmful if inhaled.	Category 4
6.1D (oral)	H302	Harmful if swallowed.	Category 4
6.3A	H315	Causes skin irritation.	Category 2
6.4A	H319	Causes serious eye irritation.	Category 2A

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.

Product Name: Tyreweld HT5SFKY6

Date of SDS: 07 March 2023

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe mist, vapours, or spray.
P264	Wash exposed skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing and eye protection.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P331	Do NOT induce vomiting.
P338	Remove contact lenses, if present and easy to do. Continue rinsing.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use CO <sub>2</sub> , dry powder, chemical foam for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

### Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Butane	10-35	106-97-8
Isobutane	10-35	75-28-5
Other non-hazardous ingredients	20-35	

### Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. If eye irritation persists: Get medical advice.
If on Skin	Wash with plenty of soap and warm water. Take off contaminated clothing and wash before re-use. If skin irritation occurs: get medical advice/attention.
If Swallowed	DO NOT induce vomiting. Never give anything to the mouth of an unconscious person. Immediately call a POISON CENTER (0800 764 766) or a doctor/physician.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position

Product Name: Tyreweld HT5SFKY6  
Date of SDS: 07 March 2023

and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

## Section 5. Fire Fighting Measures

<b>Hazard Type</b>	Flammable Aerosol
<b>Hazards from combustion products</b>	Carbon monoxide, carbon dioxide.
<b>Suitable Extinguishing media</b>	Use CO <sub>2</sub> , dry powder, or chemical foam for extinction. Always choose fire-extinguishing media appropriate for surrounding materials.
<b>Precautions for firefighters and special protective clothing</b>	Risk of exploding containers if heated. Keep water run-off out of sewers and water sources. Wear full protective gear.
<b>HAZCHEM CODE</b>	<b>2WE</b>

## Section 6. Accidental Release Measures

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

Have fire extinguishers close at hand while attending the spill.  
Collect for reclamation or absorb in vermiculite, dry sand or similar material.

Do not contaminate water sources or sewer. Dispose of according to Local Regulations.

## Section 7. Handling and Storage

### Precautions for Handling:

- Read label before use.
- Keep away from heat/sparks/open flames/hot surfaces.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wash hands thoroughly after handling.
- Avoid release to the environment.
- Wear protective clothing.

### Precautions for Storage:

- Aerosol Can: Must not be exposed to direct sunlight or temperature above 50c
- Store away from incompatible materials listed in Section 10.
- Keep out of reach of children
- Store locked up.
- Store in a well-ventilated place. Keep cool.
- Store above freezing.

## Section 8 Exposure Controls / Personal Protection

### WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA		STEL	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Butane [106-97-8]	600	1450	750	1850
Propane [74-98-6]	800		800	

Workplace Exposure Standard – Time Weighted Average (WES-TWA). *The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure.* Workplace Exposure Standard – Short-Term

Product Name: Tyreweld HT5SFKY6  
Date of SDS: 07 March 2023

Exposure Limit (WESSTEL). *The 15-minute average exposure standard.* Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

## Engineering Controls

Ensure adequate ventilation is available.

## Personal Protection

<b>Eyes</b>	Wear goggles with side shields. Avoid wearing contact lenses.
<b>Hands and Skin</b>	Use suitable protective gloves and clothing if risk of skin contact. EN374 Rubber gloves are recommended.
<b>Respiratory</b>	If ventilation is poor, use appropriate cartridge respirator.

## Section 9 Physical and Chemical Properties

<b>Appearance</b>	Aerosol White Foam Liquid
<b>Odour</b>	Slight Odour
<b>Odour Threshold</b>	Not applicable
<b>pH</b>	9.5
<b>Boiling Point</b>	Not applicable
<b>Melting Point</b>	Not applicable
<b>Freezing Point</b>	Not applicable
<b>Flash Point</b>	Lower flammable/ explosive 4.8 Upper flammable/ explosive 9.5
<b>Flammability</b>	Highly Flammable
<b>Upper and Lower Exposure Limits</b>	Not applicable
<b>Vapour Pressure</b>	Not applicable
<b>Vapour Density</b>	Not applicable
<b>Relative Density</b>	Not applicable
<b>Solubilities</b>	Slightly soluble in water, easy soluble in warm water
<b>Partition Coefficient:</b>	Not applicable
<b>Auto-ignition Temperature</b>	Not applicable
<b>Decomposition Temperature</b>	Not applicable
<b>Kinematic Viscosity</b>	Not applicable
<b>Particle Characteristics</b>	Not applicable

## Section 10. Stability and Reactivity

<b>Stability of Substance</b>	This product is stable under normal conditions.
<b>Conditions to Avoid</b>	Keep away from heat, sparks, open flames and hot surfaces
<b>Incompatible Materials</b>	Strong acids and alkalis. Oxidisers.
<b>Hazardous Decomposition Products</b>	Carbon monoxide, Carbon dioxide.

## Section 11 Toxicological Information

### Acute Effects:

<b>Swallowed</b>	May be harmful if swallowed	Unlikely due to form of product – harmful if swallowed
<b>Dermal</b>	Causes skin irritation.	Causes skin irritation.
<b>Inhalation</b>	May be harmful if swallowed and enters airways.	May be fatal if swallowed and enters airways.
<b>Eye</b>	Causes serious eye irritation.	Causes serious eye irritation.
<b>Skin</b>	Causes skin irritation.	Causes skin irritation.

**Chronic Effects:**

<b>Carcinogenicity</b>	Not applicable.
<b>Reproductive Toxicity</b>	Not applicable
<b>Germ Cell Mutagenicity</b>	Not applicable.
<b>Aspiration</b>	May be harmful if swallowed and enters airways.
<b>STOT/SE</b>	Not applicable.
<b>STOT/RE</b>	Not applicable.

**Section 12. Ecotoxicological Information**

HSNO Classes: None

<b>Persistence and degradability</b>	No data available
<b>Bioaccumulation</b>	No data available
<b>Mobility in Soil</b>	No data available
<b>Other adverse effects</b>	No data available

Do not allow to enter waterways.

**Section 13. Disposal Considerations****Disposal Method:**

**Precautions:** Dispose of waste according to Local regulations. Collected spillage and unused product must be placed in a sealable waste container for disposal through a disposal company. Ensure waste container is labelled "Hazardous Waste – Flammable, Ecotoxic"

**Disposal methods to avoid:** Do not allow product to enter sewers, streams, or waterways

**Section 14 Transport Information**

**This product is classified as a Dangerous Good in NZ ; NZS 5433:2012**

Road and Rail Transport

UN No: 1950  
Class-primary 2.1  
Packing Group PGII  
Proper Shipping Name: AEROSOLS

Air Transport

UN No: 1950  
Class-primary 2.1  
Packing Group PGII  
Proper Shipping Name: AEROSOLS

Marine Transport

UN No: 1950  
Class-primary 2.1  
Packing Group PGII  
Proper Shipping Name: AEROSOLS

**Section 15 Regulatory Information**

EPA Approval Code: **Aerosols (Flammable) – HSR002515**

HSNO Classification 2.1.2A, 6.1D(oral), 6.1D(inh), 6.3A, 6.4A,

HSNO Controls:  
Trigger quantities for this substance:

	Trigger Quantity
Approved Handler	3000L awc
Location Certificate	3000L awc
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	3000L awc
Emergency Response Plan	1000L
Secondary Containment	1000L
Restriction of Use	None

## Section 16 Other Information

### Glossary

EC <sub>50</sub>	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
LC <sub>50</sub>	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD <sub>50</sub>	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit
AWC	Aggregate water capacity

1. HSNO Approved Code of Practice: Preparation of Safety Data Sheets, September 2006.

### Disclaimer

This document has been issued by Filpro Automotive Ltd and serves as their Safety Data Sheet ('SDS'). It represents the appropriate safety and handling precautions for the product at the time of issue. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated, it does not provide any warranty as to accuracy or completeness. Please contact the country distributor, if further information is required.

Issue Date: 07 March 2023      Review Date: 07 March 2028